

**High-speed world-class model for narrow strapping**

---

**Characteristics**

---

Strapping qualities:	Polypropylene (PP)	
Strapping dimensions:	widths	5.0 and 6.0 mm / 9.0 mm
	thicknesses	0.35 – 0.65 mm / 0.45 – 0.65 mm
Strapping tension:	adjustable, 10 – 350 N	
Sealing method:	heat welding	
Power supply:	230V / 50Hz, 1 phase	
Power consumption:	0.5 kWh	
Strapping speed:	1.2 sec./cycle (approx. 50 strapping cycles/min.)	
Dimensions:	length	826 mm
	width	620 mm
	table height	810-1020 mm adjustable
Machine net weight:	160 kg	
Max. package weight:	80 kg	
Min. package size:	60W x 20H mm	
Arch size:	850 x 600 mm standard	
Temp. of working environment:	5 ~ 40°C	

## Advantages

---

- Proven quality
- Competitive price
- CE certified
- Bundles and cartons can be strapped very easily and quickly
- User-friendly and easy strapping coil change
- Easy operation, simple maintenance
- Electronic outside tension control
- Tension can be easily set with a dial
- Mobile, on wheels with brakes
- Adjustable table height (870 – 1020 mm)
- Auto strap reefed
- Strap end ejector
- Short feed sensor and foot switch included
- Photo-eye switch available as option
- Foot bar switch available as option

## Chart of types model PM312

---

Item No.	Arch size W x H (mm)	Strap width	Colour
<b>45.4201</b>	<b>550 x 400</b>	<b>5.0 mm</b>	<b>blue</b>
<b>45.4202</b>	<b>550 x 400</b>	<b>6.0 mm</b>	<b>Blue</b>
<b>45.4203*</b>	<b>550 x 400</b>	<b>9.0 mm</b>	<b>blue</b>
45.4214	650 x 500	5.0 mm	blue
45.4215	650 x 500	6.0 mm	blue
45.4216	650 x 500	9.0 mm	blue
45.4227	850 x 600	5.0 mm	blue
45.4228	850 x 600	6.0 mm	blue
45.4229	850 x 600	9.0 mm	blue

\* Machines in stock, NL-Nieuwegein.  
Availability other machines upon request.  
Different arch sizes possible.