

Technical Datas Automatic machines

| MODEL | PM308 | PM309 |
|---------------------------------------|--|---|
| Power Requirement | 110V/220V/230V/240V (50/60Hz) 1PH | 110V/220V/230V/240V (50/60Hz) 1PH |
| Strapping Speed | 27 straps/min (60Hz) | 29 straps/min (60Hz) |
| Strap Requirement | Strap width: 8 mm to 15.5 mm, Strap thickness: 0.55 - 0.75 mm | Strap width: 8 mm to 12 mm Strap thickness: 0.55 - 0.75 mm |
| Tension Range | 10 to 70 kg | 7 to 70 kg |
| Dimensions (W) x (D) x (H) | 1430 x 620 x 1540 mm {arch size: 850mm(W)*600mm(H)} | 1430 x 620 x 1540 mm {arch size: 850mm(W)*600mm(H)} |
| Table Height | 810 mm | 810 mm |
| Machine Net Weight | 220 kg | 220 kg |
| Maximum Package Weight | 100 kg | 100 kg |
| Minimum Package Size | 100W x 20H mm | 130W x 20H mm |
| Strap Core Inner Diameter | 200mm / 280mm (interchangeable) | 200mm / 280mm (interchangeable) |
| Power Consumption | 1.2 kW | 1.2 kW |
| Temperature of working environment | 5 - 40 C° | 5 - 40 C° |