

Semi-automatic strap feeding system

Semi-automatic strap feeding system for steel strapping



Characteristics

Strapping qualities:	Uniflex and Ultraflex max. 1100 N/mm ² / 160'000 psi						
Stapping dimensions: widths	13.0 – 32.0 mm / 1/2 – 1 1/4"						
thicknesses	0.38 – 1.27 mm / .015050"						
Tools recommended:	Flat packages: A3H, A384, A380, A383						
	Coils: A480, A482, A483						
Feeding units:	E101 pneumatically operated						
	E201 electrically operated, with an automatic strap retracting						
	system for automatic re-feeding						
Dispensers:	HA1 for strapping widths up to 19 mm oscillated						
	HA3 for strapping widths 19, 25 & 32 mm ribbon						
Longitudinal displacements:	stationary without sword stationary (EFS1XX)						
	stationary with sword stationary (EFS2XX)						
	moveable without sword movement on rail or on portal						
	frame (EFS4XX)						
	moveable with sword movement on rail or on portal						
	frame (EFS5XX)						
	, , ,						

Advantages

- Strap feeding systems reduce the total strapping time substantially compared to manual feeding methods
- Very often labour work can be saved
- The rugged feeding systems have been designed for continuous and shift operations demanding a high working reliability
- Easy handling allows comfortable operation
- A very wide variety of different feeding systems in any dimensions are available
- · Customer friendly control system; keyboard and display show all information and messages in the language required by the customer
- Every feeding system is built for the requirement of the customer
- Supplied with a suspension device with a running wagon and the balancer for the strapping tool



Semi-automatic strap feeding system

Chart of types model EFS

Model	Feeding unit E101 E201	Longitudinal displacement					Sword		Special	
		E201	stationary	on ra powered	ail manual	on portal powered	frame manual	without	with	design
EFS100	Χ		Χ					Χ		
EFS101		Χ	Χ					Х		
EFS104	Χ		Χ					X		Coils
EFS200	Χ		X						Χ	
EFS201		Χ	Χ						Χ	
EFS204	Χ		X						Χ	Coils
EFS400	Χ					X		X		
EFS401		Χ				Χ		Х		
EFS402		Χ					X	Х		
EFS403	Χ						Х	Х		
EFS404	Χ					Χ		X		Coils
EFS405	Х			Х				Х		
EFS406		Χ		X				X		
EFS407		Χ			Х			Х		
EFS408	Χ				X			X		
EFS409	Х			Х				Χ		Coils
EFS500	Χ					X			Χ	
EFS501		Χ				Х			Х	
EFS502		X					Χ		Χ	
EFS503	Х						Х		Х	
EFS504	Χ					Χ			Χ	Coils
EFS505	Х			Х					Х	
EFS506		X		X					Χ	
EFS507		Х			Х				Х	
EFS508	Χ				X				Χ	
EFS509	Х			Х					Х	Coils

Accessories

- Fixed bottom strap guide
- Lower wooden runner
- Manual horizontal strap displacement
- Foot pedal to start the feeding and the retracting operations, recommended in case of variety of packaging sizes
- High platform for head maintenance and easy operation
- Orange flash light = strap feeder is travelling
- Transformer for electric supply different than 400 V / 50 Hz