

Pneumatic steel strap pusher type tensioner, for round objects



Technical data

Strapping qualities	Uniflex and Ultraflex max. 1.100 N/mm ² - 160'000 psi	
Strapping dimensions	widths	19,0 – 32,0 mm - 3/4 – 1 1/4"
	thicknesses	0,63 – 1,27 mm - .025 - .050"
Weight	4,35 kg - 9.6 lbs	
Strap tension	8.500 N - 1,900 lbs (6 bar - 87 psi)	
Seals	Overlap seals	
Sealing	In combination with sealer models A412 or A461	
Suspension	Eye bolt for standard applications	

Features

- This rugged tool permits a high strap tension up to 8.500N / 1,900 lbs
- High tension speed
- Stops automatically when the max tension force is reached
- No tension loss, due its free-wheeling tension system
- For safety reasons, the strap (tension) can be released at any time by pressing the black safety push button
- (Very) low noise operation
- This light tool is ideal for non-stationary use
- Particularly suitable for applications in the steel- and steel processing industry

24 July 2020

Chart of types, model A452

Item No.	Model	Uniflex™ and Ultraflex™ max. 1.100 N/mm ² / 160'000 psi				Max. Tension		Tension speed	
		Width		Thicknesses					
		mm	inch	mm	inch	N	lbs	mm/s	Inch/s
13.4210	A452/19-32 /0,63-1,27	19-32	¾ - 1 ¼"	0,63-1,27	.025-.050	8.500	1,900	150	5.9